Mela MuteTM Acoustic Foam Super Wedge

SPEC SHEET

- Low Frequency Absorber
- Super Lightweight
- Easy to Install
- Class A Fire Rated
- Decorative & Paintable
- Non-Fibrous & No Itch



Material:	Open Cell Melamine Foam					
Patterns:	Deep Wedges, Porous, Semi-Rigid, Non-Fibrous					
Features:	Easy to Install, Absorbs Low Frequencies, Controls Echo & Reverb, Decorative, Lightweight, Class A Fire Rated, Paintable, Non-Fibrous, Non-Toxic					
Application:	Testing Chambers, Recording Studios, Broadcast Studios, Offices, Conference Rooms, Restaurants, Music Rooms, Universities, Hospitals, Schools, Houses of Worship, Theaters, Multi-Purpose Rooms, Government & Municipal Facilities					
Thickness:	4", 6", & 8"					
Size:	12" × 12"					
Weight	4": 0.70lbs 6": 1.00lbs 8": 1.35lbs					
Color:	White, Light Grey, Dark Grey					
Temperature Rating:	-40°F to 350°F					
Flammability:	ASTM E84, Class A Flame Spread: 10 Smoke Developed: 50					
Installation:	P329 Spray Adhesive or Construction Adhesive					

Noise Reduction Coefficient

Size	Test Mount	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
4" Mela Mute™ Super Wedge	A-Mount	0.33	0.67	1.19	1.18	1.23	1.24	1.05
6" Mela Mute™ Super Wedge	A-Mount	0.22	1.07	1.27	1.34	1.27	1.15	1.25
8" Mela Mute™ Super Wedge	A-Mount	0.39	1.05	1.44	1.38	1.33	1.19	1.35





